

a complete act of
balabcing

PS Series

Platform Scale

- Heavy Duty Structure
- Stainless Steel Top
- Overload Protection
- Optional MS Top Available
- SS Back Rail



AN ISO 9001 - 2000 COMPANY

Industrial & Commercial Scale

PS SERIES

PS SERIES



Model	DS		PS	
Platform size	400x400mm	500x500mm	600x600mm	750x750mm
Capacity	50kg 55/65/75kg 100kg	100kg 200kg	100kg 200kg 300kg	300kg 500kg
No. of load cells	01	01	01	01
Structure type	Pipe	Pipe	Pipe	Pipe
Top cover	Standard-ss Optional-ms	Standard-ss Optional-ms	Standard-ss Optional-ms	Standard-ss Optional-ms
Back grill	Yes	Yes	Yes	Yes
Over load cell	150%	150%	150%	150%

- Capacity range from 50 kg to 500kg
- Sturdy MS square pipe structure provides equal Load distribution
- SS Top (Standard) up to 600 x 600 mm Structure; MS Top For 750 x 750 mm
- Rugged structure for industrial use with extra impact loading and Overloading capacity
- High Resolution Load Cell with Over Load stoppers and Transport Protection
- Shock absorbers from rubber to reduce shock on load cell

Industrial Heavy Duty Scale

Model	SS / SX		
Platform size	900x900mm	1000x1000mm	1250x1250mm
Capacity	300kg 500kg 1000kg 2000kg	300kg 500kg 1000kg 2000kg	300kg 500kg 1000kg 2000kg
No. of load cells	04	04	04
Structure type	*C*channel	*C*channel	*C*channel
Top cover	Standard-ss Optional-ms	Standard-ss Optional-ms	Standard-ss Optional-ms
Back grill	Yes	Yes	Yes
Over load cell	150%	150%	150%

* Other customized sizes are also available

- Capacity 500 kg, 1T, 2T, 3T & 5T
- Extra 'C' channel structure provides equal Load distribution
- Standard Mild Steel checkered Top cover and Back grill for support
- Over Load stoppers and Transport Protection
- Rocker pin foot assembly provides stability and durability (SX series)
- SS Series – Single Load Cell system - High Resolution Jumbo Load Cell
- SX Series – Four Load Cell system - Single point beam Load Cell
- Optional Weighing Indicators
- Easy access junction

FS SERIES



SS SERIES

Indicators



IND - SS



IND - YT3

Capacity	0~99999 Kg.
Readability	Class III / II
Divisions	Max. 30,000d
Display	1" / 0.56" RED LED
Power	AC/Rechargeable battery

- Adjustment & calibration through key board
- Tare & Preset Tare value
- Manual Storage and accumulation of Weighing records; stores up to 200 records
- Simple counting function available
- Simple Check weighing function is available
- AC / DC power supply, with built-in rechargeable battery
- Battery provides up to 50 hrs of continuous use.
- 7 Segment; 6 digit LED, 6 status indication
- Compatible with any kind of Weighing Platforms
- Connect up to 4 load cells

Crane Scale



Capacity	100 kg to 20T
Readability	Compatible to class III
Display	0.56" Red LED
Op. Temp.	-10 °c to +50°c
Tare	100%
Optional	Remote Control

- Maximum Capacity : 300kg, 500kg, 1T, 2T, 3T, 5T & 10T
- Readability : 100g, 200g, 500g, 1kg, 1kg, 2kg & 5kg
- Big easy readable red LED Display
- Accuracy : compatible to OIML class III
- Accuracy is verified by three bits so, very much reliable
- Light weight, smaller body cubage; so, portable to carry & install anywhere
- Low voltage indicator for battery voltage.
- Full function remote controller (optional)



ENDEAVOUR INSTRUMENT PVT. LTD.

307, Anand Chambers, Nr. Stadium Under Bridge,
Naranpura, Ahmedabad - 380 009 INDIA.
Phone: +91-79-2644 0606 / 7 Fax: +91-79-2642 1221
Email : eipl@endeavourweigh.com

www.endeavourweigh.com